

## Ronaprime I34EM


Epoxy Primer for Ronabond Epoxy Flooring

### Description




An epoxy polyamide primer for use in conjunction with Ronabond EPF 106HB, Ronabond PU 500 and Ronaflex Sealants.



### Uses

-  Specially formulated high viscous product for use with Ronabond epoxy or polyurethane coatings or any high build system that requires extra bonding properties.

### Benefits

-  Excellent adhesion to concrete
-  Compatible with most surfaces and top coats
-  Easy mix and apply

## Specification Clause

The Epoxy Polyamide Primer shall be Ronaprime 134EM by Ronacrete (Far East) Limited. All materials to be applied strictly in accordance with manufacturer's instructions.

### Technical Data

Recommended Dry Film Thickness	50 $\mu$
No. of Coats	1
No. of Components	2
Estimated Coverage @ 50 $\mu$	4 – 5 m <sup>2</sup> /litre
Mixing Ratio	3:1 by volume of Part A & Part B
Thinning Ratio	Max. 25% by volume
Pot Life	30 mins
Shelf Life	12 months
Drying Time	Touch dry : 45 minutes Overcoating : 4 - 5 hours

### Packaging

Ronaprime 134EM is supplied in 4 litres or 20 litres pack.

## Application (\*Please Refer to the Method Statement and MSDS)

### Surface Preparation

As required. For more specific application, please consult **Ronacrete (FE) Ltd.**

### Mixing

Stir containers separately and mix both contents with slow speed power mixer for 5 minutes before use.

### Thinning

Maximum 25% by volume with Ronabond EP Epoxy Thinner.

### Method of Application

Roller or brush.

### Safety

Strict precautions as the use of other combustible, volatile solvent must be observed.

### Technical Service and Support

Ronacrete provide free technical advice and support during design and installation of all systems for flooring, concrete repair, bonding, bedding and waterproofing. If you need any further information including method statement or additional technical data sheet, contact the Ronacrete Technical Department on (852) 2866 4365 or visit our web site [www.ronacrete.com.hk](http://www.ronacrete.com.hk).

### Guarantee

Ronacrete products are guaranteed fit for purpose and of merchantable quality.

Ref: RFE-DS076 Issue 5 05.01.16

## Coatings

### Disclaimer

The information herein is liable to modification in the light of experience and ongoing development. Before use you are advised to check with Ronacrete (Far East) Ltd. to ensure this is the latest issue. Any person or company using the product without first enquiring about its suitability for the intended use does so at their own risk and Ronacrete (Far East) Ltd. can accept no responsibility for the results or for any loss or damage arising out of such use. Unless otherwise stated all data shown is typical laboratory results achieved in ideal conditions, site results may differ.

Ronacrete (Far East) Ltd. is the Marble Patron Member of Hong Kong Green Building Council (HKGBC) in 2015. For the latest membership status of Ronacrete (Far East) Ltd. in HKGBC, please refer to the HKGBC official website.



Ronacrete (Far East) Limited 16/F., 3 Lockhart Road, Wanchai, Hong Kong SAR  
Tel : (852) 2865 5872 Fax : (852) 2865 5568 E-mail : [ronafix@ronacrete.com](mailto:ronafix@ronacrete.com)

[www.ronacrete.com.hk](http://www.ronacrete.com.hk)