

1. IDENTIFICATION OF PRODUCT AND COMPANY

Product: Ronagrount EPG - Part A
Company : Sika Hongkong Limited
Rm. 1507-12, Block A, New Trade Plaza, 6 On Ping St., Shatin, N.T.
Tel. / Fax.: +852 2686 8108 / +852 2645 3671

2. COMPOSITION

Name	Cas No.	Proportion
Bisphenol A epoxy resin	25068-38-6	High
Aliphatic Glycidyl Ether	68609-97-2	Low
Other ingredients determined not to be hazardous		To 100 %

V.High >60, High 30 - 60, Med 10 - 29, Low 1 - 9, V.Low <1
All the constituents of this product are listed on the Australian Inventory of Chemical Substances (AICS) and National Registration Authority (NRA) approved active constituents.

To be used with Ronagrount EPG - Part B

3. HAZARDS IDENTIFICATION

Hazard Category: Xn Harmful, Xi Irritant
Risk Phrases: R21/22 Harmful in contact with skin and if swallowed
R43 May cause sensitisation by skin contact.
D.G. Class: Not classified as dangerous goods
Subsidiary Risk: Nil
Poison Schedule: S 5
This product is a Schedule Poison S 5 and must be stored, maintained and used in accordance with the relevant regulation.

4. FIRST AID MEASURES

Ingestion: If swallowed do not induce vomiting. Rinse mouth with water, give glass of water and seek medical attention.

Eye contact: Immediately irrigate with copious quantities of water for at least 15 minutes. Eyelids to be held open. Seek immediate medical assistance.

Skin contact: Remove contaminated clothing and footwear. Wash skin thoroughly with water. If swelling, redness, blistering or irritation occurs seek medical

SIKA HONGKONG LTD

Rm. 1507-12, 15/F, Block A, New Trade Plaza, 6 On Ping Street, Shatin, New Territories, Hong Kong
Phone: +852 2686 8108 · Fax: +852 2645 3671 · www.sika.com.hk

Inhalation: attention.
Remove victim from exposure to fresh air. If breathing difficulty, apply artificial respiration and seek medical attention.

Note to Physician: Treat the patient symptomatically.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water, Foam, Dry chemical powder, Carbon dioxide.
Specific Hazards: The material is stable under normal conditions. Hazardous polymerisation can occur on heating. On decomposition gives off carbon dioxide, carbon monoxide and other gases. Incompatible with alkalies, acids and strong oxidizers.
Fire Fighters: Wear positive pressure, self-contained breathing apparatus and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

Small Spills: Shut off all possible ignition sources. Wear protective equipment to prevent skin and eye contamination. Clean with absorbent material like sand, soil, vermiculite or any other inert material. Avoid contamination of drains, sewerage and waterways. Collect and seal in properly labelled containers for disposal as per local council statutory codes.
Large Spills: Shut off all possible ignition sources. Wear protective equipment to prevent skin and eye contamination. Clean with absorbent material like sand, soil, vermiculite or any other inert material. Avoid contamination of drains, sewerage and waterways. Collect and seal in properly labelled containers for disposal as per local council statutory codes. If contamination of crops, waterways, drains or sewerage has occurred, advise Emergency Services or State Department of Agriculture.

7. HANDLING AND STORAGE

Storage: Store in the closed, original container in a cool ventilated area. Keep containers tightly closed when not in use. Keep away from explosives, food, oxidising agents and organic peroxides. This product is a Scheduled Poison S5 and must be stored, maintained and used in accordance with the relevant regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits: No value assigned for this specific product by the National Occupational and Safety Commission (Worksafe Australia). However, supplier recommended Hygiene Standard as under

TWA STEL Carcinogen Notices

Material	TWA		STEL		Notices
	ppm	mg/m3	ppm	mg/m3	
Bisphenol A resin		N/E*	N/E*	N/E*	N/E* -
Aliphatic glycidyl ether		N/E*	N/E*	N/E*	N/E*

N/E* - No Exposure Standard has been established for this product.

Eng. Controls:	Special ventilation is not normally required due to the low volatility of the product at normal temperature. However, in the operation of certain equipment or at elevated temperatures, mists or vapours may be generated and exhaust ventilation should be provided to maintain airborne concentration levels below the exposure standards or where no exposure standard is allocated, as low as reasonably practicable.
Personal Protection:	Use overalls, safety shoes, safety goggles, rubber or chemical resistance gloves and respirator if required.
Manufacturing, Packaging & Transport:	Avoid skin and eye contact and the inhalation of vapour. Wear overalls, safety goggles and impervious gloves. Available information suggests that the Gloves made from PVC should be suitable for intermittent contact. However due to variations in glove construction and local conditions, the final assessment should be made by the user. If inhalation risk exists, wear organic vapour respirator meeting requirements of AS/NZS 1715 and 1716. Always wash hands with soap and water before smoking, eating, drinking or using toilet facilities.
Preparations & use of product:	Repeated exposure may cause allergic disorders. Sensitive workers should use protective clothing. Avoid contact with eyes and skin. Do not inhale mist or vapours. After each day's use, wash gloves, safety goggles and all the contaminated clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

pearance :	White paste
Solubility :	Insoluble in water
Specific Gravity :	1.45 - 1.50
Boiling Point :	More than 200 deg. C
Rel.Vapour Density (air=1) :	> 1
Melting Range :	Not established
Vapour Pressure (20o C) :	Less than 0.01 Pa
Decomposition Temp.(o C) :	More than 200 deg. C
Flash Point (o C) :	More than 200 deg. C (ASTM D 93)

Flammability Limits (%) :	Not established
Ph :	Not applicable
Autoignition Temp. (o C) :	Not established
% Volatile by Volume :	Nil
(All above values are Typical Values only)	
VOC:	< 420 grams per litre

10. STABILITY AND REACTIVITY

The product is stable under normal conditions and use.

11. TOXICOLOGICAL INFORMATION

No adverse health effects are expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms that may arise if the product is mishandled are:

Acute Effects:

Ingestion: Harmful if swallowed. May cause gastrointestinal discomfort and irritation.

Eye: Brief contact may cause mild irritation to eyes.

Skin: Mild irritant and poorly absorbed through the skin. Prolonged and repeated contact may cause sever irritation and/or dermatitis

Inhaled: Not hazardous at ambient temperatures. Vapours generated at elevated temperatures or when inhaled repeatedly may cause irritation to nose, throat and respiratory tract.

Long Term Effects:

Repeated skin contact and inhalation may result in sensitisation in some individuals. May cause allergic reaction, dermatitis or asthma like symptoms. Follow good working practice. Avoid ingestion, inhalation, eye and skin contact. Wash hands with soap and water before eating, drinking, smoking or using toilet facilities.

Acute & Chronic:

Negative in a battery of mutagenicity assays.

Toxicity:

No evidence of carcinogenicity was observed in long term studies of rats.

No developmental nor reproductive effects in rat and rabbit.

12. ECOLOGICAL INFORMATION

Avoid contamination of drains, sewerage, creeks and waterways.

Not toxic to aquatic organisms

13. DISPOSAL CONSIDERATIONS

Dispose all empty containers as per State & Council Regulation. Do not dispose near waterways, vegetation and tree roots. Empty containers and product should not be burned.

14. TRANSPORT INFORMATION

N. No. : Not Allocated
Shipping Name : Not Applicable
Class : Not classified as dangerous goods
Subsidiary Risk : Nil
Packaging Group : Not Applicable
Hazchem Code : Not Applicable
EPG : Not Applicable
Segregation : Not to be loaded with explosives, oxidising agents or organic peroxides.

For road, marine and air transport this product is not classified as dangerous goods within the context of National and International Transport Regulation.

15. REGULATORY INFORMATION

The National Model Regulations for the Control of Workplace Hazardous Substances [NOHSC : 10005 (1999)].

The National Standard for the Storage and Handling of Workplace Dangerous Goods [NOHSC : 1015 (2001)].

Type of Regulated Paint under the Air Pollution Control (Volatile Organic Compounds) Regulation of Hong Kong: Other sealants

16. OTHER INFORMATION

The information given here is to the best of our knowledge true and accurate and is provided solely for making safety assessments. It is not a sales specification or an indication of suitability for a particular use.

1. IDENTIFICATION OF PRODUCT AND COMPANY

Product: Ronagrout EPG - Part B
Company: Sika Hongkong Limited
Rm. 1507-12, Block A, New Trade Plaza, 6 On Ping St., Shatin, N.T.
Tel. / Fax.: +852 2686 8108 / +852 2645 3671

2. COMPOSITION

Name	Cas No.	Proportion
Polyaminoamide	68082-29-1	High

Other ingredients determined

not to be hazardous To 100 %

V.High >60, High 30 - 60, Med 10 - 29, Low 1 - 9, V.Low <1

All the constituents of this product are listed on the Australian Inventory of Chemical Substances (AICS) and National Registration Authority (NRA) approved active constituents.

To be used with Ronagrout EPG - Part A

3. HAZARDS IDENTIFICATION

Hazard Category: Xn Harmful, Xi Irritant
Risk Phrases: R21/22 Harmful in contact with skin and if swallowed
R43 May cause sensitisation by skin contact.
D.G. Class: Not classified as dangerous goods
Subsidiary Risk: Nil
Poison Schedule: S 5
This product is a Schedule Poison S 5 and must be stored, maintained and used in accordance with the relevant regulation.

4. FIRST AID MEASURES

Ingestion: If swallowed do not induce vomiting. Rinse mouth with water, give glass of water and seek medical attention.
Eye contact: Immediately irrigate with copious quantities of water for at least 15 minutes. Eyelids to be held open. Seek immediate medical assistance.
Skin contact: Remove contaminated clothing and footwear. Wash skin thoroughly with water. If swelling, redness, blistering or irritation occurs seek medical attention.
Inhalation: Remove victim from exposure to fresh air. If breathing difficulty, apply artificial respiration and seek medical attention.

Note to Physician: Treat the patient symptomatically.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water, Foam, Dry chemical powder, Carbon dioxide.

Specific Hazards: The material is stable under normal conditions. Hazardous polymerisation can occur on heating. On decomposition gives off carbon dioxide, carbon monoxide and other gases. Incompatible with alkalis, acids and strong oxidizers.

Fire Fighters: Wear positive pressure, self-contained breathing apparatus and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

Small Spills: Shut off all possible ignition sources. Wear protective equipment to prevent skin and eye contamination. Clean with absorbent material like sand, soil, vermiculite or any other inert material. Avoid contamination of drains, sewerage and waterways. Collect and seal in properly labelled containers for disposal as per local council statutory codes.

Large Spills: Shut off all possible ignition sources. Wear protective equipment to prevent skin and eye contamination. Clean with absorbent material like sand, soil, vermiculite or any other inert material. Avoid contamination of drains, sewerage and waterways. Collect and seal in properly labelled containers for disposal as per local council statutory codes. If contamination of crops, waterways, drains or sewerage has occurred, advise Emergency Services or State Department of Agriculture.

7. HANDLING AND STORAGE

Storage: Store in the closed, original container in a cool ventilated area. Keep containers tightly closed when not in use. Keep away from explosives, food, oxidising agents and organic peroxides. This product is a Scheduled Poison S5 and must be stored, maintained and used in accordance with the relevant regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits:
Occupational and recommended

No value assigned for this specific product by the National Safety Commission (Worksafe Australia). However, supplier Hygiene Standard as under

TWA STEL Carcinogen Notices

Material	TWA		STEL		Notices
	ppm	mg/m3	ppm	mg/m3	
Polyaminoamide	N/E*	N/E*	N/E*	N/E*	-
Tris-2,4,6 (Dimethyl-aminomethyl) Phenol	N/E*	N/E*	N/E*	N/E	

N/E* - No Exposure Standard has been established for this product.

Eng. Controls:	Special ventilation is not normally required due to the low volatility of the product at normal temperature. However, in the operation of certain equipment or at elevated temperatures, mists or vapours may be generated and exhaust ventilation should be provided to maintain airborne concentration levels below the exposure standards or where no exposure standard is allocated, as low as reasonably practicable.
Personal Protection:	Use overalls, safety shoes, safety goggles, rubber or chemical resistance gloves and respirator if required.
Manufacturing, Packaging & Transport:	Avoid skin and eye contact and the inhalation of vapour. Wear overalls, safety goggles and impervious gloves. Available information suggests that the Gloves made from PVC should be suitable for intermittent contact. However due to variations in glove construction and local conditions, the final assessment should be made by the user. If inhalation risk exists, wear organic vapour respirator meeting requirements of AS/NZS 1715 and 1716. Always wash hands with soap and water before smoking, eating, drinking or using toilet facilities.
Preparations & use of product:	Repeated exposure may cause allergic disorders. Sensitive workers should use protective clothing. Avoid contact with eyes and skin. Do not inhale mist or vapours. After each day's use, wash gloves, safety goggles and all the contaminated clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance :	Buff paste
Solubility :	Partially soluble in water
Specific Gravity :	1.6 - 1.7 @ 25 DEG. C
Boiling Point :	More than 200 deg. C
Rel.Vapour Density (air=1) :	> 1
Melting Range :	Not established
Vapour Pressure (20o C) :	Less than 0.01 Pa
Decomposition Temp.(o C) :	More than 200 deg. C
Flash Point (o C) :	More than 200 deg. C (ASTM D 93)
Flammability Limits (%) :	Not established

Ph : Not applicable
Autoignition Temp. (°C) : Not established
% Volatile by Volume : Nil
(All above values are Typical Values only)
VOC: < 420 grams per litre

10. STABILITY AND REACTIVITY

The product is stable under normal conditions and use.

11. TOXICOLOGICAL INFORMATION

No adverse health effects are expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms that may arise if the product is mishandled are:

Acute Effects:

Ingestion: Harmful if swallowed. May cause gastrointestinal discomfort and irritation.

Eye: Brief contact may cause mild irritation to eyes.

Skin: Mild irritant and poorly absorbed through the skin. Prolonged and repeated contact may cause severe irritation and/or dermatitis

Inhaled: Not hazardous at ambient temperatures. Vapours generated at elevated temperatures or when inhaled repeatedly may cause irritation to nose, throat and respiratory tract.

Long Term Effects:

Repeated skin contact and inhalation may result in sensitisation in some individuals. May cause allergic reaction, dermatitis or asthma like symptoms. Follow good working practice. Avoid ingestion, inhalation, eye and skin contact. Wash hands with soap and water before eating, drinking, smoking or using toilet facilities.

Acute & Chronic:

Negative in a battery of mutagenicity assays.

Toxicity:

No evidence of carcinogenicity was observed in long term studies of rats.

No developmental nor reproductive effects in rat and rabbit.

12. ECOLOGICAL INFORMATION

Avoid contamination of drains, sewerage, creeks and waterways.

Product may be toxic to some aquatic organisms.

13. DISPOSAL CONSIDERATIONS

Dispose all empty containers as per State & Council Regulation. Do not dispose near waterways, vegetation and tree roots. Empty containers and product should not be burned.

14. TRANSPORT INFORMATION

UN. No. :	Not Allocated
Shipping Name :	Not Applicable
Class :	Not classified as dangerous goods
Subsidiary Risk :	Nil
Packaging Group :	Not Applicable
Hazchem Code :	Not Applicable
EPG :	Not Applicable
Segregation :	Not to be loaded with explosives, oxidising agents or organic peroxides.

For road, marine and air transport this product is not classified as dangerous goods within the context of National and International Transport Regulation.

15. REGULATORY INFORMATION

The National Model Regulations for the Control of Workplace Hazardous Substances [NOHSC : 10005 (1999)].

The National Standard for the Storage and Handling of Workplace Dangerous Goods [NOHSC : 1015 (2001)].

Type of Regulated Paint under the Air Pollution Control (Volatile Organic Compounds) Regulation of Hong Kong: Other sealants

16. OTHER INFORMATION

The information given here is to the best of our knowledge true and accurate and is provided solely for making safety assessments. It is not a sales specification or an indication of suitability for a particular use.

1. IDENTIFICATION OF PRODUCT AND COMPANY

Product: Ronagroust Colour Pack
 Company: Sika Hongkong Limited
 Rm. 1507-12, Block A, New Trade Plaza, 6 On Ping St., Shatin, N.T.
 Tel. / Fax.: +852 2686 8108 / +852 2645 3671

2. COMPOSITION

Ingredients:	Name	Cas No.	Proportion
	Bisphenol A epoxy resin	25068-38-6	High
	Aliphatic Glycidyl Ether	68609-97-2	Low
	Other ingredients determined not to be hazardous		To 100 %

V.High >60, High 30 - 60, Med 10 - 29, Low 1 - 9, V.Low <1

All the constituents of this product are listed on the Australian Inventory of Chemical Substances (AICS) and National Registration Authority (NRA) approved active constituents.

HAZARDS IDENTIFICATION

Hazard Category: Xi Irritant
Risk Phrases: R36/38 Irritating to Skin and eyes
 R43 May cause sensitisation by skin contact.
D.G. Class: Not classified as dangerous goods
Subsidiary Risk: Nil
Poison Schedule: S 5
 This product is a Schedule Poison S 5 and must be stored, maintained and used in accordance with the relevant regulation.

4. FIRST AID MEASURES

Ingestion: If swallowed do not induce vomiting. Rinse mouth with water, give glass of water and seek medical attention.
Eye contact: Immediately irrigate with copious quantities of water for at least 15 minutes.
 Eyelids to be held open. Seek immediate medical assistance.
Skin contact: Remove contaminated clothing and footwear. Wash skin thoroughly with water. If swelling, redness, blistering or irritation occurs seek medical attention.

Inhalation: Remove victim from exposure to fresh air. If breathing difficulty, apply artificial respiration and seek medical attention.

Note to Physician: Treat the patient symptomatically.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water, Foam, Dry chemical powder, Carbon dioxide.

Specific Hazards: The material is stable under normal conditions. Hazardous polymerisation can occur on heating. On decomposition gives off carbon dioxide, carbon monoxide and other gases. Incompatible with alkalies, acids and strong oxidizers.

Fire Fighters: Wear positive pressure, self-contained breathing apparatus and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

Small Spills:

Shut off all possible ignition sources. Wear protective equipment to prevent skin and eye contamination. Clean with absorbent material like sand, soil, vermiculite or any other inert material. Avoid contamination of drains, sewerage and waterways. Collect and seal in properly labelled containers for disposal as per local council statutory codes.

Large Spills:

Shut off all possible ignition sources. Wear protective equipment to prevent skin and eye contamination. Clean with absorbent material like sand, soil, vermiculite or any other inert material. Avoid contamination of drains, sewerage and waterways. Collect and seal in properly labelled containers for disposal as per local council statutory codes. If contamination of crops, waterways, drains or sewerage has occurred, advise Emergency Services or State Department of Agriculture.

7. HANDLING AND STORAGE

Storage:

Store in the closed, original container in a cool ventilated area. Keep containers tightly closed when not in use. Keep away from explosives, food, oxidising agents and organic peroxides. This product is a Scheduled Poison S5 and must be stored, maintained and used in accordance with the relevant regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits: No value assigned for this specific product by the National Occupational and Safety Commission (Worksafe Australia). However, supplier recommended Hygiene Standard as under;

TWA STEL Carcinogen Notices

Material	TWA		STEL		Notices
	ppm	mg/m3	ppm	mg/m3	
Bisphenol A resin	N/E*	N/E*	N/E*	N/E*	-
Aliphatic glycidyl ether	N/E*	N/E*	N/E*	N/E*	-

Eng. Controls: **N/E* - No Exposure Standard has been established for this product.** Special ventilation is not normally required due to the low volatility of the product at normal temperature. However, in the operation of certain equipment or at elevated temperatures, mists or vapours may be generated and exhaust ventilation should be provided to maintain airborne concentration levels below the exposure standards or where no exposure standard is allocated, as low as reasonably practicable.

Personal Protection: Use overalls, safety shoes, safety goggles, rubber or chemical resistance gloves and respirator if required.

Manufacturing, Packaging & Transport: Avoid skin and eye contact and the inhalation of vapour. Wear overalls, safety goggles and impervious gloves. Available information suggests that the gloves made from PVC should be suitable for intermittent contact. However due to variations in glove construction and local conditions, the final

The information contained herein and any other advice are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. The information only applies to the application(s) and product(s) expressly referred to herein. In case of changes in the parameters of the application, such as changes in substrates etc., or in case of a different application, consult Sika's Technical Service prior to using Sika products. The information contained herein does not relieve the user of the products from testing them for the intended application and purpose. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

assessment should be made by the user. If inhalation risk exists, wear organic vapour respirator meeting requirements of AS/NZS 1715 and 1716.

Always wash hands with soap and water before smoking, eating, drinking

or using toilet facilities.

Preparations & use of product: should
Repeated exposure may cause allergic disorders. Sensitive workers
use protective clothing. Avoid contact with eyes and skin. Do not inhale
mist
or vapours. After each day's use, wash gloves, safety goggles and all the
contaminated clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance :	Viscous paste various colours
Solubility :	Insoluble in water
Specific Gravity @ 25 deg. C :	1.40 - 1.60
Boiling Point :	More than 200 deg. C
Rel.Vapour Density (air=1) :	8
Melting Range :	Not established
Vapour Pressure (20o C) :	Less than 0.01 Pa
Decomposition Temp.(o C) :	More than 200 deg. C
Flash Point (o C) :	More than 200 deg. C (ASTM D 93)
Flammability Limits (%) :	Not established
Ph :	Not applicable
Autoignition Temp. (o C) :	Not available
% Volatile by Volume :	Nil
(All above values are Typical Values only)	
VOC:	< 420 grams per litre

10. STABILITY AND REACTIVITY

The product is stable under normal conditions and use.

11. TOXICOLOGICAL INFORMATION

No adverse health effects are expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms that may arise if the product is mishandled are:

Acute Effects:

Ingestion: Harmful if swallowed. May cause gastrointestinal discomfort and irritation.

Eye: Brief contact may cause mild irritation to eyes.

Skin: Mild irritant and poorly absorbed through the skin. Prolonged and repeated contact may cause severe irritation and/or dermatitis

Inhaled: Not hazardous at ambient temperatures. Vapours generated at elevated temperatures or when inhaled repeatedly may cause irritation to nose, throat and respiratory tract.

Long Term Effects: Repeated skin contact and inhalation may result in sensitisation in some individuals. May cause allergic reaction, dermatitis or asthma like symptoms.

Follow good working practice. Avoid ingestion, inhalation, eye and skin contact. Wash hands with soap and water before eating, drinking, smoking or using toilet facilities.

Acute & Chronic: Negative in a battery of mutagenicity assays.

Toxicity: No evidence of carcinogenicity was observed in long term studies of rats.

No developmental nor reproductive effects in rat and rabbit.

Acceptable Daily Intake (ADI) for humans is 0.01 mg/kg/day.

12. ECOLOGICAL INFORMATION

Avoid contamination of drains, sewerage, creeks and waterways.

Not toxic to aquatic organisms.

13. DISPOSAL CONSIDERATIONS

Dispose all empty containers as per State & Council Regulation. Do not dispose near waterways, vegetation and tree roots. Empty containers and product should not be burned.

14. TRANSPORT INFORMATION

UN. No. :	Not Applicable
Shipping Name :	Not Applicable
Class :	Not Applicable
Subsidiary Risk :	Not Applicable
Packaging Group :	Not Applicable
Hazchem Code :	Not Applicable
EPG :	Not Applicable
Segregation :	Not Applicable

For road, marine and air transport this product is not classified as dangerous goods within the context of National and International Transport Regulation.

15. REGULATORY INFORMATION

The National Model Regulations for the Control of Workplace Hazardous Substances [NOHSC : 10005 (1999)].

The National Standard for the Storage and Handling of Workplace Dangerous Goods [NOHSC : 1015 (2001)].

Type of Regulated Paint under the Air Pollution Control (Volatile Organic Compounds) Regulation of Hong Kong: Other sealants

16. OTHER INFORMATION

Date of Preparation :	30.11.09
Date of Revision :	30.11.14
Reasons for Issue :	New Review

MSDS's are updated frequently. Please ensure you have the current copy. This MSDS summarises at the date of issue our best knowledge of health and safety hazard information of the product, and in particular how to handle and use the product in the workplace. Since Vivacity Engineering Pty Ltd cannot anticipate or control the conditions under which the product may be used each user must, prior to usage, review this MSDS in the context to use MSDS's are updated frequently. Please ensure you have the current copy. This MSDS summarises at the date of issue our best knowledge of health and safety hazard information of the product, and in particular how to handle and use the product in the workplace. Since Vivacity Engineering Pty Ltd cannot anticipate or control the conditions under which the product may be used each user must, prior to usage, review this MSDS in the context to use and handling of the product in the workplace. If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact Vivacity Engineering Pty Ltd. Our responsibility for the product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.